

dual lens digital camera

# The world's smallest 10X optical zoom digital camera.

In a dynamic intersection of performance and sophistication comes the Kodak EasyShare V610 dual lens digital camera. Two precision crafted lenses within its amazingly slender body deliver 10X optical zoom power. And with Bluetooth® wireless technology, you can take a picture of friends at the party and send it to them right away. Introducing the up close and personal V610 – the world's smallest 10X optical zoom digital camera.

## Remarkable picture quality

- Kodak Retina dual lens technology makes the V610 the world's smallest 10X optical zoom digital camera
- Create stunning quality prints up to 76 x 102 cm (30" x 40") with 6.1 MP
- Remarkable image quality features such as Kodak Perfect Touch technology and advanced noise reduction make it possible
- Get exceptional clarity and sharpness with its two professional quality Schneider-Kreuznach C-Variogon lenses
- Create great shots time after time with 22 scene modes including panorama stitch, and 3 color modes
- Get rich, vibrant color under a variety of lighting conditions with the exclusive Kodak color science chip

# Powerfully simple video features

- Record VGA video (640 x 480) at 30 fps with sound
- Zoom during video and avoid camera shake with image stabilization
- Capture more video while using less memory with MPEG-4 compression
- Make prints from video with multiple pictures on a 10 x 15 cm (4" x 6") print
- Select single frames to e-mail to family and friends

# The simple way to share

- When you're with friends, use the embedded Bluetooth wireless technology to send them pictures
- View and share your pictures with clarity on the large 7.1 cm (2.8") high resolution, indoor/outdoor display featuring a wide viewing angle
- Share your favorite shots anytime, anywhere, using the on-camera Share button, and use the Favorites feature to keep your special pictures close







The best part about your digital camera? Your pictures. So when you print your pictures – whether you choose to do it at home, online, or right where you shop – look to Kodak. Because when you trust your prints to Kodak, you can be sure you're getting quality that's truly exceptional and pictures that will last.

Learn more about printing choices at www.kodak.com/go/printandshare



#### Standard features

CCD resolution (effective pixels) – 6.36 megapixels (2934x2171)

Image resolution (recorded pixels) – 6.1 megapixels (2848x2144)

Picture quality

6.0 MP - best (2832x2128) prints up to 50x76 cm (20"x30")

5.3 MP - best 3:2 (2832x1888) optimized ratio for 10x15 cm (4"x6") prints

4.0 MP - better (2304x1728) prints up to 50x76 cm (20"x30")

3.1 MP – good (2048x1536) prints up to 28x36 cm (11"x14")

1.1 MP - e-mail (1200x900) small prints

Still format - JPEG/EXIF v 2.21

Lens – dual lens technology; 10X optical zoom, 38–114 mm (35 mm equiv.) f/3.9-f/4.4 130-380 mm (35 mm equiv.) f/4.8

Advanced digital zoom - 4X advanced digital zoom, total zoom range 40X

Aperture - f/3.9-f/7.1 (wide), f/4.8-f/8.0 (tele) Shutter speed - 8-1/1200 sec.

LCD - 7.1 cm (2.8") high resolution (230K pixels) indoor/outdoor

## Creative performance controls

Scene modes – auto, portrait, panorama left-right, panorama right-left, sport, landscape, close-up, night portrait, night landscape, snow, beach, text, fireworks, flower, manner/museum, self-portrait, party, children, backlight, panning shot, candlelight, sunset, custom

Color modes – high color, natural color, low color, sepia, black and white

Burst mode – 1.6 fps, maximum 8 images in any quality mode

Click to capture - 0.3 sec.

Shot to shot - 1.1 sec.

Video mode – continuous MPEG-4 compressed video with audio capture and playback

Video resolution – VGA (640x480 pixels) at 30 fps, VGA long at 30 fps, QVGA (320x240 pixels) at 30 fps

Video length – continuous up to 80 min. based on memory capacity

Video features – 10X zoom during video with image stabilization and auto focus; print thumbnails and snapshots from video, on-camera trim video editing

Video format - QuickTime

Auto focus – TTL-AF, multi-zone AF, center spot AF Auto focus control – single AF, continuous AF

Focus range – wide: 0.6 m (2')-infinity wide (macro): 0.05 m (2")-0.7 m (2.3') (wide) tele: 1.6 m (5.2')-infinity tele (macro): 0.7 m (2.3')-1.7 m (5.6')

Sensitivity – ISO equivalent 64-400 (auto) and 64, 100, 200, 400, 800 (manual)

White balance – auto, daylight, tungsten, fluorescent, open shade

Exposure metering – auto: TTL-AE; selectable: multipattern, center-weighted, center-spot

Exposure compensation –  $\pm 2.0$  EV with 0.3 EV steps Long time exposure – 0.5-8 sec.

#### Ease of use features

Histogram – display on live view and review Built-in flash – auto, off, fill, digital red-eye reduction Flash range –

wide: ISO 280 - 0.6 m (2')-3.4 m (11.2') tele: ISO 400 - 0.6 m (2')-3.3 m (10.8')

Review options - 1X-8X magnify with pan, fast scroll, multi-up, slide show, album, picture info, erase, protect, crop, copy, image storage, Share/print, view by, and Favorites

Editing - selectable red-eye reduction, Kodak Perfect Touch technology, on-camera cropping, blurry image detection, panorama image stitch mode

Favorites - on-camera picture storage

Dedicated buttons – power, shutter, still, scene, movie, Favorites, review, delete, menu, Share, and flash

Sound – customizable sound themes: default, jazz lounge, secret agent

Auto picture rotation and orientation

Software – works with Kodak EasyShare software Storage – 32 MB internal memory: available, SD/MMC card expansion slot

Self-timer -10 seconds, 2 seconds, and 2 picture

#### Additional features

Bluetooth technology functionality - Bluetooth 2.0 EDR Bluetooth technology transfer method - object push protocol

Bluetooth technology transfer rate – up to 3 Mbps
Dock compatibility – works with optional Kodak
EasyShare photo printer 500, Kodak EasyShare
printer dock plus series 3, Kodak EasyShare printer
dock series 3, Kodak EasyShare photo frame dock 2,
and Kodak EasyShare camera dock series 3'

ImageLink print system compatible

PictBridge enabled

I/O interface - A/V output (NTSC or PAL, userselectable), exclusive Kodak camera dock/printer dock interface, digital (USB 2.0) connector

Power – Kodak Li-Ion rechargeable digital camera battery – KLIC-7001

Lens protection – built in lens barrier Tripod mount – 1/4 in. standard Weight – without batteries: 160 g (5.6 oz.) Dimensions – WxHxD: 111x55.5x23.2 mm (4.4x2.2x0.9 in.)

Warranty - one year

## Minimum system requirements

Windows 2000 or XP OS 600 MHz processor or greater 128 MB RAM Internet Explorer 5.01 or higher PowerMac or PowerBook G3, G4, G5; iMac; eMac; or iBook computer Macintosh OS X 10.3 or higher Safari 1.1 or higher 128 MB RAM

### Minimum hardware requirements

200 MB hard drive disk space available CD-ROM drive Available USB port

Color monitor, 1024x768 display resolution, thousands of colors, minimum

#### Package contents

Kodak EasyShare V610 dual lens digital camera USB and audio/video cables and adapter Kodak Li-lon rechargeable digital camera battery – KLIC-7001

5V AC adapter with power cord for in-camera battery charging

Carry strap

Camera case

Kodak EasyShare software

Getting started kit

Custom camera insert for optional Kodak EasyShare photo frame dock 2

Custom camera insert for optional Kodak EasyShare camera and printer docks

### Ordering information

| Kodak EasyShare V610 | ) dual lens digital camera |
|----------------------|----------------------------|
| (U.S. and Canada)    | XXX XXXX                   |

## Recommended accessories

| Kodak EasyShare printer dock plus series 3xxx xxxx |
|--|
| Kodak color cartridge and photo paper kitxxx xxxx  |
| Kodak SD memory cards                              |
| 256 MBxxx xxxx                                     |
| 512 MBxxx xxxx                                     |
| 1 GBxxx xxxx                                       |
| Kodak Li-lon rechargeable digital camera           |
| battery KLIC-7001                                  |
| Kodak Li-lon universal battery                     |
| charger K7500Cxxx xxxx                             |
| Kodak EasyShare picture viewerxxx xxxx             |
| Kodak 8-in-1 card readerxxx xxxx                   |
| Kodak EasyShare printer dock travel bagxxx xxxx    |
|  |

 $\dot{*}32$  MB internal memory/28 MB available for picture storage (1 MB equals one million bytes).

†Compatibility identified by this yellow symbol. (Kodak dock adapter kit D-22 required to enable compatibility with Kodak EasyShare printer dock plus, printer dock, printer dock 6000, and camera dock 6000.)



For more information on the Kodak EasyShare V610 dual lens digital camera, visit www.kodak.com/go/easyshare











